

DC LED Modules

Ultra high efficiency led light-bar



Linear Series



- ◆ High efficiency up to 170lm/W
- ◆ Poke in wiring connectors
- ◆ Within 3-step Macadam
- ◆ Various CCT available
- ◆ Optional 90 & 95 CRI

P/N	Size	Voltage -Vdc		Current -mA		Power -W		Flux	Efficiency	CCT	CRI
	mm	Typ	Max	Typ	Max	Typ	Max	Lm	Lm/W	K	-
RL-CM280x24A1203H007-840	280*24	34.8	39.6	200	450	7	18	1180	170	4000	80
RL-CM280x24A0409H007-840	280*24	11.6	13.2	600	1350	7	18	1180	170	4000	80
RL-CM560x24A1206H014-840	560*24	34.8	39.6	400	900	14	36	2360	170	4000	80
RL-CM560x24A0809H014-840	560*24	23.2	26.4	600	1350	14	36	2360	170	4000	80
RL-VM600x24A0706H008-840	600*24	24	-	340	-	8	-	1000	125	4000	80
RL-VM600x24A0706H016-840	600*24	24	-	680	-	16	-	1840	115	4000	80


Note: 1-Variou CCT available (2700-6000K) ; RL-XXXXXXXXXXXXXXXX-840 (8-80CRI;40-4000K CCT)

2-Typical Optical-electronic parameters above @ Ta=25°C

Application




Linear Light



Troffer Light



Panel Light



Wall Light

Dimension --mm

