

# AC LED Modules

Driverless led engine solution



## Round Series



- ◆ AC input directly
- ◆ EMI compliance
- ◆ THDI<15%
- ◆ Surge protection : 2.5KV
- ◆ High-pot level : 1.5KV

P/N	Size	Input	Power	PF	Flux	Efficiency	CCT	CRI	Dimming
	mm	Vac	W	-	Lm	Lm/W	K	-	-
RL-HMD100A2802H016-830N	Ø100	230	16	0.95	1600	100	3000	80	-
RL-HMD100A2802H016-830T	Ø100	230	16	0.95	1600	100	3000	80	TRIAC
RL-HMD100A2802H016-830A	Ø100	230	16	0.95	1600	100	3000	80	0-10V
RL-LMD100A1404H016-830T	Ø100	120	16	0.95	1600	100	3000	80	TRIAC
RL-LMD100A1404H016-830A	Ø100	120	16	0.95	1600	100	3000	80	0-10V
RL-HMD070A2801H009-830N	Ø70	230	9	0.95	900	100	3000	80	-
RL-HMD070A2801H016-830T	Ø70	230	16	0.95	1600	100	3000	80	TRIAC
RL-HMD070A2801H016-830A	Ø70	230	16	0.95	1600	100	3000	80	0-10V
RL-LMD070A1402H016-830T	Ø70	120	16	0.95	1600	100	3000	80	TRIAC
RL-LMD070A1402H016-830A	Ø70	120	16	0.95	1600	100	3000	80	0-10V

**Note:** 1-Variou CCT available ( 2700-6000K ) ; RL-XXXXXXXXXXXXXXXX-830X ( 8-80CRI;30-3000K CCT )

2-Typical Optical-electronic parameters above @ Ta=25°C

### Application




Downlight



Ceiling Light



Pendant Light



Wall Light

### Dimension --mm

