

1815 Fully Encapsulated Silicone Flexible Wall Washing Lamp Data Sheet



- Using silicone extrusion process, 18*15Mini size design
- Uniform light emission, good appearance consistency
- Anti-yellowing, high temperature resistance, corrosion resistance, weak acid and alkali resistance
- Good flexibility, small size, light weight, easy installation
- Food-grade environmentally friendly silicone material.
- Waterproof grade IP67
- 5 years warranty


Technologies

- ON/OFF, Dali, PWM, 0-10V, DMX2PWM Dimmer, Radio Frequency control


Application

- This product is suitable for engineering projects, park lighting, buildings, hotels, shopping malls, swimming pools, and other decorative lighting purposes.


Color Options




Dimensions




Beam Angle




Sectional drawing



Recommended Accessories



Side exit end cap



Bottom Exit end cap



Direct Exit End cap




End cap



Bendable Profile



Clip



cable

Product Specifications

P/N	LED Quantity	CCT K	CRI	LED (SM)	LUMENS (lm/m)	Vf. (V.)	Current (mA/M)	Power (W/M)	Cut Length (MM)	Max Run (M)
RL-FV2412036283512-830-FWD1815	2835	2700	80/90	36	960	24	500	12	27.7	5
		3000			960					
		4000			1020					
		6500			1020					

Other Specifications

Protection grade	IP67
Working temperature (°C)	-25~+60
Standard length (°C)	-25~+70
Maximum cascade length(m)	5
Maximum cascade length (m)	5
weight	/

Remark

- The test environment temperature is 25±2°C;
- The above data are typical values, the actual parameters of the product may be different from the typical data; the data is subject to change without notice;
- The above "/" means that this parameter is not required for the time being.


Applied Standards




Installation

Note :Due to the different types and attributes of neon lights, please refer to the, line marks for the bending radius

① Bending Direction & Min. radius





② Side bending prohibited




Mounting with aluminium profiles

Install with the screws provided. Do not use screws of other types or sizes that do not meet requirements.




Install correctly




1

Use M3 screw every 200mm




2




Schematic diagram of electrical connection


1. Monochrome temperature wiring diagram 1: Power + lamp belt connection mode



2. Monochrome temperature wiring diagram 2: Power supply + dimmer + lamp belt connection




3. RGB wiring diagram: Power + controller + light belt connection mode




Schematic diagram of electrical connection

4.SPI wiring diagram: Power + controller + light belt connection mode



5.DMX512 wiring diagram: Power + controller + light belt connection





Specialized
LED Strip Manufacturer

Shenzhen
Relight Technology Co.,Ltd

6th Floor, Building A, Guancheng Industrial Park, Gongming Town,
Guangming District, Shenzhen, China

Tel: 86 0755 3369 1713
Web: www.relight-tech.com
E-mail: Sales@relight-tech.com